

Power LogOn®

USB Desktop Reader PLR-1A



This reader is primarily used on desktops within many different businesses and industries. The heavy base makes it ideal for one hand operation for smart card insertion and removal.



- ISO 7816 contact reader
- Vertical card insertion slot
- One hand operation with heavy weight base
- Ideal for desktop and POS use
- In field firmware updates
- Compliant with all major smart cards
- Compliant with all relevant industry standards

Technical Data



Host	USB	<ul style="list-style-type: none"> • Full speed USB 2.0 (12 Mbps) • USB Bus powered device • CCID compliant • Cable 2 m long with USB type A connector
Smart Card	Contact ISO-7816	<ul style="list-style-type: none"> • T=0, T=1 protocol support • Communication speed (PPS, FI parameter) up to 500 kbps • Frequency up to 8 MHz (PPS, DI parameter) • Supports ISO 7816 smart card class A, AB • 100,000 Insertions
Human	Optical	<ul style="list-style-type: none"> • One green LED
Dimensions	L x W x H (mm)	• 95 x 64 x 85
Weight	[g]	• 440
Operating Conditions	Temperature [°C] Humidity [%]	<ul style="list-style-type: none"> • 0 to 50 • 90 (non-condensing)
Approvals	Functional	<ul style="list-style-type: none"> • FCC Class B part 15, cULus, CE, VCCI • USB-IF • ICES-003 Issue 4 • EMV 2000 Level 1 upon request • RoHS, WEEE
Operating Systems		<ul style="list-style-type: none"> • Windows® 7, Vista, XP, Server 2003, 2000, ME, 98SE • Windows® 7, Vista, XP, Server2003 (AMD64/EMT64) • Windows® CE 3.0, 4.1, 4.2, 5.0, 6.0 • MacOS, Solaris, Linux 32/64-bit

Technical data are subject to change without notice.

Order your

Administrator Starter Kit

now only \$497

An easy and affordable way to test
Power LogOn and card issuance
on your network.



Order online at:

www.Access-Smart.com

Or call Toll Free (877) 795-6466

Everything you need in one kit

- 6 contact smartcards
- 2 USB Readers
- Manager and CardMaker Software
- 30 Demo Licenses, 1 Full License
- 10 Peel and Stick Labels
- 1.5 hours Tech Support
- User Manual



Powered by
Smartcard
Technology®

© ALL INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED "AS IS"; Access Smart ASSUMES NO RESPONSIBILITY FOR ITS ACCURACY AND/OR COMPLETENESS. Power LogOn, Access Smart, and Powered by Smartcard Technology are registered trademarks licensed by Access Smart, LLC. All other trademarks and trade names are the properties of their respective companies. In no event will Access Smart be liable for damages arising directly or indirectly from any use of the information contained in this document.

Customize Your Solution



USB Desktop Reader



PCMCIA Reader



USB Slim Reader



ExpressCard Reader



Secure Flash Drive



Smartcards

System Requirements

Card Administrator

Operating System:

Windows® 7, Vista, XP, 2000, 2000 Server, 2003 Server or 2008 Server.

Computer:

Pentium® 233 MHz or higher, or compatible; CD-ROM drive; VGA or higher graphics; 128MB of RAM; Available USB, PCMCIA or ExpressCard port; and 8 GB available hard disk space.

Employee's Computer

Operating System:

Windows® 2000, XP Professional/Home Edition, Vista, or Windows 7.

Computer:

Pentium® 233 MHz or higher, or compatible; CD-ROM drive; VGA or higher graphics; 128MB of RAM; Available USB, PCMCIA or ExpressCard port; and 70MB available hard disk space.